

TOP HUNG AWNING WINDOW

ALSPEC's range of Top Hung Awning windows are ideal for suburban housing, multi-unit residential, hotels and semi commercial applications.

The Top Hung Awnings can integrate with a number of ALSPEC's commercial framing systems by using different awning adaptors.

The 35mm sash is available as an overlapping or inset sash.

The 443 30mm sash sits inset of the framing and can offer a flush appearance.

Various options for single and double glazing are available.

All Top Hung Awnings are operated with Chainwinders. With the use of our Chainwinder adaptor, insect and security screens can easily be added from the inside of the building.

Specifications:

Glazing Options: 4mm > 24mm IGU

ASW AWNING SASH

Maximum height	1500mm o/a sash
Minimum height	450mm o/a sash
Maximum width	1200mm o/a sash
Minimum width	350mm o/a sash
Maximum perimeter	4.5m
Maximum area	1.5m ²
Maximum sash weight	40kg

443 AWNING SASH SINGLE GLAZED

Maximum height	1000mm o/a sash
Minimum height	290mm o/a sash
Maximum width	1000mm o/a sash
Minimum width	350mm o/a sash
Maximum area	1.0m ²
Maximum sash weight	18kg

443 AWNING SASH DOUBLE GLAZED

Maximum height	1000mm o/a sash
Minimum height	290mm o/a sash
Maximum width	1000mm o/a sash
Minimum width	350mm o/a sash
Maximum area	1.0m ²
Maximum sash weight	40kg



Call 1300 ALSPEC

www.alspec.com.au

alspec
ALUMINIUM SYSTEMS
SPECIALISTS